

Kevin Avants M 505 780 1061  
info@avantsstone.com  
www.avantsstone.com

AVANTS STONE  
PORPHYRY SALES  
AND INSTALLATION

Avants STONE is a division of AvantGARDENS Inc. | GB98 #83938 , ICPI Certified, AIA Santa Fe | Authorized Contractor & Certified Installer



## Patagonia Sierra Porphyry

Patagonia Sierra Porphyry has a beautiful mix of reddish brown, gray and ochre gold. These colors enhance the gray tones and add to a balanced appearance. Available in a wide variety of sizes for diverse applications, it is suited for use in city streets, sidewalks, courtyards, pedestrian plazas, auto courts and patios. Porphyry lends itself to an old world, hand-crafted look while meeting modern standards. Natural surface meets ADA requirements for both smoothness and slip resistance. Inherent strength withstands harsh winter climates and resists snow melt chemicals.

Desired for its color, prized for its durability, it's the perfect paving surface. Most of all, it's beautiful.

*"Considered over the life of the project, natural stone will use far less of the earth's resources than a comparable manufactured product. Public paving is the area where this is the most extreme situation and where stone should be used as a first priority." – Michael Heap*

**Kevin Avants** M 505 780 1061

**info@avantsstone.com**

**www.avantsstone.com**



**AVANTS STONE**

**PORPHYRY SALES  
AND INSTALLATION**



Avants STONE is a division of AvantGARDENS Inc. | GB98 #83938 , ICPI Certified, AIA Santa Fe | Authorized Contractor & Certified Installer

**Patagonia Sierra Available Sizes**

	Size	Thickness
<b>Cubes</b>	2 1/4" x 3 1/4"	2 3/4" - 3 1/2"
	3 1/4" - 4 1/4"	3 1/4" - 4 1/4"
<b>Snap Cut Pavers</b>	4" x 4"	3/4" - 1 5/8"
	4" x 4"	1 1/4" - 2 1/4"
	4" x 4"	2 1/4" - 3 1/4"
Snap Cut Pavers	4" x R/L	1/2" - 1 1/4"
	4" x R/L	1 1/4" - 2 1/4"
	4" x R/L	2 1/4" - 3 1/4"
	4" x R/L	3 1/4" - 4 1/4"
Snap Cut Pavers	6" x R/L	1/2" - 1 1/2"
	6" x R/L	1 1/4" - 2 1/4"
	6" x R/L	2 1/4" - 3 1/4"
Snap Cut Pavers	8" x R/L	1/2" - 1 1/2"
	8" x R/L	1 1/4" - 2 1/4"
	8" x R/L	2 1/4" - 3 1/4"
Snap Cut Pavers	10" x R/L	1/2" - 1 1/2"
	10" x R/L	1 1/4" - 2 1/4"
	10" x R/L	2 1/4" - 3 1/4"
Snap Cut Pavers	12" x R/L	1/2" - 1 1/2"
	12" x R/L	1 1/4" - 2 1/4"
	12" x R/L	2 1/4" - 3 1/4"
<b>Sawn Edge Pavers</b>	6" x R/L	3/4" - 1 1/2"
	6" x R/L	1 1/2" - 2 1/4"
Sawn Edge Pavers	8" x R/L	3/4" - 1 1/2"
	8" x R/L	1 1/2" - 2 1/4"
Sawn Edge Pavers	10" x R/L	3/4" - 1 1/2"
	10" x R/L	1 1/2" - 2 1/4"
Sawn Edge Pavers	12" x R/L	3/4" - 1 1/2"
	12" x R/L	1 1/2" - 2 1/4"
Sawn Edge Pavers	16" x R/L	3/4" - 1 1/2"
	16" x R/L	1 1/2" - 2 1/4"
<b>Smolleri</b>	1 1/4"-3 1/4" x min 4"	1 1/4" - 3 1/4"



ASTM DATA Patagonia Storm Gray	Measure	Result
ASTM C97 Density	lb/cf3	160.5
ASTM C170 Compressive Strength	psi	27557
ASTM C880 Flexural Strength	psi	38100
ASTM C99 Modulus of Rupture	psi	3042
ASTM C1028 Static Coefficient of Friction		0.62
ASTM C241 Abrasion Resistance		70.92
ASTM C97 Absorption		0.0042